

# इंटरनेट

# मानक

## Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 4007-2-6 (1983): Terminals for Electronic Equipment, Part 2: Detail Terminals, Section 6: Terminal, Non-Insulated, with Insulated Captive Spring Cap, Tapped Hole Panel Mounting, Type TSL 1 [LITD 3: Electromechanical Components and Mechanical Structures for Electronic Equipment]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE



Indian Standard

SPECIFICATION FOR  
TERMINALS FOR ELECTRONIC EQUIPMENT

PART 2 DETAIL SPECIFICATION FOR TERMINALS

Section 6 Terminal, Non-Insulated, with Insulated Captive Spring  
Cap, Tapped Hole Panel Mounting, Type TSL 1


**1. Scope** — This standard ( Part 2/Sec 6 ) covers detail requirements of terminals, non-insulated with insulated captive spring cap, tapped hole panel mounting, type TSL 1 and shall be read in conjunction with IS : 4007 ( Part 1 )-1982 ' Specification for terminals for electronic equipment : Part I General requirements and tests ( first revision ) '.

**2. Climatic Test Severities**

Temperature severity	55, 85°C	10, 70°C
Damp heat ( steady state )	56 days	21 days
Damp heat ( cyclic )	6 cycles	2 cycles
Low air pressure	4.4 kPa	30 kPa
Vibration	10 to 55 Hz, Duration 6 hours Amplitude displacement — 0.75 mm	
Impact	500 m/s <sup>2</sup> , 5 minutes	

**3. Outline Drawing and Dimensions** — See Table 1.

TABLE 1 DIMENSIONS OF TERMINAL TYPE TSL 1



**Note 1** — Dimensions are in millimetres.

**Note 2** — Unless otherwise specified, tolerances are  $\pm 0.40$  mm.

**Note 3** — Drawing depicts only general characteristics and is not intended to limit specific manufacturing processes. Shape of insulated portion is optional.

**Note 4** — Screw threads according to IS : 4218 ( Part 2 )-1967.

EXPLANATORY NOTE

This standard is based on JSS 52710-Jan 1974 ' Specification for terminals, captive screw cap and captive spring loaded ', published by Ministry of Defence. In addition to climatic severities specified in JSS-52710-Jan 1974 the climatic severities for commercial usage have been included in this standard.

Adopted 18 November 1983

© March 1984, BIS

Gr 1